

FLYNN

Appl. No. 10/715,368

December 18, 2006

RECEIVED
CENTRAL FAX CENTER

DEC 18 2006

AMENDMENTS TO THE CLAIMS:

Please amend claim 6 as follows.

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (previously presented) Apparatus for processing data, said apparatus comprising:
a processor operable to perform data processing operations, said processor being operable to generate a performance control signal indicative of a desired data processing performance level of said processor; and
at least one further circuit, responsive to said performance control signal, to support said desired data processing performance level of said processor; wherein while responding to a change in performance control signal corresponding to a change from a first desired data processing performance level to a second desired data processing performance level, said at least one further circuit supports data processing at at least one intermediate data processing performance level and said processor temporarily operates at said at least one intermediate data processing performance level during said change.
2. (original) Apparatus as claimed in claim 1, wherein said one or more further circuits include a voltage controller operable to generate a power signal for said processor at a plurality of different voltage levels.
3. (original) Apparatus as claimed in claim 1, wherein said one or more further circuits include a clock generator operable to generate a clock signal with a selectable clock frequency.

FLYNN

Appl. No. 10/715,368

December 18, 2006

4. (original) Apparatus as claimed in claim 2, wherein, in response to an increase in desired data processing performance level, said clock generator increases clock signal frequency to an intermediate clock signal frequency when said voltage controller is generating a power signal with a voltage level sufficient to support said intermediate clock signal frequency.
5. (original) Apparatus as claimed in claim 1, wherein one or more priority signals serve to trigger said further circuit change to support a predetermined data processing performance level independently of said performance control signal.
6. (currently amended) A method of processing data, said method comprising the steps of:
- performing data processing operations with a processor, said processor being operable to generate a performance control signal indicative of a desired data processing performance level of said processor; and
- in response to said performance control signal, operating one or more further circuits so as to support said desired data processing performance level of said processor; wherein while responding to a change in performance control signal corresponding to a change from a first desired data processing performance level to a second desired data processing performance level, said ~~said~~ operating step includes supporting data processing at at least one intermediate data processing performance level and said processor temporarily operates at said at least one intermediate data processing performance level during said change.

FLINN

Appl. No. 10/715,368

December 18, 2006

7. (original) A method as claimed in claim 6, wherein said one or more further circuits include a voltage controller operable to generate a power signal for said processor at a plurality of different voltage levels.
8. (original) A method as claimed in claim 6, wherein said one or more further circuits include a clock generator operable to generate a clock signal with a selectable clock frequency.
9. (original) A method as claimed in claim 7, wherein, in response to an increase in desired data processing performance level, said clock generator increases clock signal frequency to an intermediate clock signal frequency when said voltage controller is generating a power signal with a voltage level sufficient to support said intermediate clock signal frequency.
10. (original) A method as claimed in claims 6, wherein one or more priority signals serve to trigger said further circuit change to support a predetermined data processing performance level independently of said performance control signal.
11. (previously presented) Apparatus for processing data, said apparatus comprising:
a processor operable to perform data processing operations, said processor being operable to generate a performance control signal indicative of a desired data processing performance level of said processor; and
at least one further circuit, responsive to said performance control signal, for supporting said desired data processing performance level of said processor; wherein while responding to a change in performance control signal corresponding to a change from a first desired data

FLYNN

Appl. No. 10/715,368

December 18, 2006

processing performance level to a second desired data processing performance level, said at least one further circuit comprising a means for supporting data processing at at least one intermediate data processing performance level and said processor temporarily operates at said at least one intermediate data processing performance level during said change.